

**Terminals for Hazardous Areas (ATEX)**

Elmex Terminals are designed and approved for use in potentially explosive environments and are classified for surface installation, Group II, category 2 and Zone 1 and 2.

RATING FOR ATEX				
Terminal	Rated Voltage	Maximum Rated Current	Conductor size(sq mm) F=>Flexible R=>Rigid	Torque
KUT 2.5	750 V	24 A	Rated c/s 2.5 ,0.5-2.5 F, 0.5-4 R	0.5
KUT 4	750 V/550 V-TS32	32 A	Rated c/s 4,0.5-4 F, 0.5-6 R	0.5
KULT 4	750 V	32 A	Rated c/s 4,0.5-4 F, 0.5-6 R	0.5
KUT 6	750 V/550 V-TS32	41 A	Rated c/s 6,0.5-6 F, 0.5-10 R	0.8
KULT 6	750 V	41 A	Rated c/s 6,0.5-6 F, 0.5-10 R	1.4
KUT 10	550 V	57 A	Rated c/s 10 ,1.5-10 F,1.5-16 R	1.2
KULT 1	1000 V/750 V-TS32	57 A	Rated c/s 10 ,1.5-10 F,0.5-16 R	1.5
KUT 16	750 V	76 A	Rated c/s 16,6-16 F,6-25 R	1.2
KUT 25	750 V	101 A	Rated c/s 25,6-16 F,6-25 R	2.3
KUT 35	750 V	125 A	Rated c/s 35 ,10-35 F,10-35 R	3.0
KUT 50	1000 V	150 A	Rated c/s 50 ,16-50 F,16-70 R	8.0
KUT 95	1000 V	232 A	Rated c/s 95 ,25-95 F,25-120R	20
MBT 4	420 V	24 A	Rated c/s 2.5 ,0.5-2.5 F,0.5-4R	0.5
KUDD 4	275 V	21 A	Rated c/s 2.5 ,0.5-2.5 F,0.5-4R	0.4
KU2D 4	275 V	21 A	Rated c/s 2.5 ,0.5-2.5 F,0.5-4R	0.4
KU2D 4S	275 V	21 A	Rated c/s 2.5 ,0.5-2.5 F,0.5-4R	0.4
DU3D 4	275 V	18 A	Rated c/s 2.5 ,0.5-2.5 F,0.5-4R	0.5
DUSD 4	275 V	18 A	Rated c/s 2.5 ,0.5-2.5 F,0.5-4R	0.5
KUTSD 6	550 V	35 A	Rated c/s 6 ,0.5-6 F,0.5-10 R	1.4
KSTD6WS	550 V	41 A	Rated c/s 6 ,0.5-6 F,0.5-10 R	0.8
KUTD 10	420 V	61 A	Rated c/s 10 ,1.5-10 F,1.5-16 R	1.2
KAT M4	750 V	57 A	Rated c/s 10 ,0.5-10 F,0.5-10R	1.2
KBT M4	750 V	57 A	Rated c/s 10 ,0.5-10 F,0.5-10R	1.2
KAT M5	750 V	76 A	Rated c/s 16 ,0.5-16F,0.5-16 R	2.0
KBT M5	750 V	76 A	Rated c/s 16 ,0.5-16F,0.5-16 R	2.0
DPBB 70	1000 V	192 A	Rated c/s 70 10-70 F,10-70 R	3.0
KUDF 4	420 V	6.3 A	Rated c/s 2.5 ,0.5-2.5 F,0.5-4R	0.4
KUDDF 4	420 V	6.3 A UT/20 A LT	Rated c/s 2.5 ,0.5-2.5 F,0.5-4R	0.4
UBDF 4	750 V	6.3 A	Rated c/s 4 ,0.5-4 F,0.5-6 R	0.5
KUFH 4	750 V	6.3 A	Rated c/s 10 ,0.5-4 F,0.5-6 R	0.5
KUF 10	750 V	10 A	Rated c/s 6 ,0.5-10 F,0.5-10 R	1.4
KULTD 6	550 V*	32 A	Rated c/s 6 ,0.5-6 F,0.5-10 R	1.0
KLTD M4	750 V	32 A	Rated c/s 2.5 ,0.5-6 F,0.5-10 R	2.0
SUT 4	420 V	24 A	Rated c/s 4 ,0.5-2.5 F,0.5-4 R	0.5
NET 4	420 V	32 A	Rated c/s 4 ,0.5-4 F,0.5-4 R	0.5
PET 4	420 V	30 A	Rated c/s ,0.5-4 F,0.5-4 R	0.5
DEBB50	1000 V	150 A	Rated c/s 50 ,10-50 F,10-50 R	3.0
DPBB120	1000 V**	250 A	Rated c/s 120 ,25-120 F,25-120 R	6.0
CST 70BB	750 V**	192 A	Rated c/s 70 F & R	6.0
CST 185BB	750 V**	353 A	Rated c/s 185 F & R	14
ET 6	-	-	Rated c/s 6 ,1.5-6F.1.5-10 R	0.8
ET 10	-	-	Rated c/s 10 ,1.5-10.1.5-16 R	1.2

ET 16	-	-	Rated c/s 16 ,6-16 F,6-25 R	1.2
ET 35	-	-	Rated c/s 35 ,6-35 F,6-35 R	3.0
EBT 2.5	-	-	Rated c/s 2.5 ,0.5-2.5 F,0.5-4 R	0.5
EBT 4	-	-	Rated c/s 4 ,0.5-4 F,0.5-6 R	0.5
EBT 6	-	-	Rated c/s 6 ,1.5-6 F,0.5-10 R	1.2
EBT 4 TWIN	-	-	Rated c/s 4 ,0.5-4 F,0.6 R	0.5