



DESCRIPTION	KULT 4	KULT 6	KULT 1							
TERMINAL PITCH	6 mm (0.24 Inch)	8 mm (0.31 Inch)	10 mm (0.39 inch)							
HEIGHT x WIDTH in mm (Inch)	58.5 x 52 (2.30 x 2.05)	58.5 x 52 (2.30 x 2.05)	58.5 x 52 (2.30 x 2.05)							
RATED CROSS SECTION	4 sq mm	6 sq mm	10 sq mm							
CONNECTION Flexible	0.5 sq mm - 4 sq mm	0.5 sq mm - 6 sq mm	1.5 sq mm - 10 sq mm							
POSSIBILITY Rigid	0.5 sq mm - 6 sq mm	0.5 sq mm - 10 sq mm	1.5 sq mm - 16 sq mm							
WIRE STRIPPING LENGTH	12 mm	12 mm	12 mm							
TYPE OF CONNECTION	2 screw clamp & 1 tapped hole for cross connection	2 screw clamp & 1 tapped hole for cross connection	2 screw clamp & 1 tapped hole for cross connection							
RATINGS	IEC 60947-7-1 1000 V/32 A/4 sq mm/0.5 Nm 600 V/35 A/10-24 AWG/7 Lbln	800 V/41 A/6 sq mm/1.4 Nm 600 V/45 A/8-24 AWG/12 Lbln	1000 V/57 A/10 sq mm/1.2 Nm 600 V/65 A/6-16 AWG/17 Lbln							
SCREW SIZE	M4	M4	M4							
	 SPRING LOADED	 SPRING LOADED	 SPRING LOADED							
TERMINAL TYPE	CAT #	STD. PKG.	WT/STD.PKG-KG	CAT #	STD. PKG.	WT/STD.PKG-KG	CAT #	STD. PKG.	WT/STD.PKG-KG	
END PLATE	KULT4	100	1.45	KULT6	100	1.92	KULT1	100	2.70	
PARTITION PLATE WITHOUT FOOT	KPSL	100	0.38	KPSL	100	0.38	KPSL	100	0.38	
PARTITION PLATE WITH FOOT	KBZF	100	0.75	KBZF	100	0.75	KBZF	100	0.75	
SUPPORT FOR PROTECTION COVER	UHDD	100	0.80	UHDD	100	0.80	UHDD	100	0.80	
PROTECTION COVER	PCK 3	100	7.00	PCK 3	100	7.00	PCK 3	100	7.00	
END CLAMPS	SCKN	100	0.80	SCKN	100	0.80	SCKN	100	0.80	
	SCUN	100	0.94	SCUN	100	0.94	SCUN	100	0.94	
	SCUSL	50	0.63	SCUSL	50	0.63	SCUSL	50	0.63	
	SCUDD	50	0.64	SCUDD	50	0.64	SCUDD	50	0.64	
SHORTING LINK ASSEMBLY	- 2 WAY	CCLA4K-2W	100	0.60	CCLA6K-2W	100	0.60	CCLA1LK-2W	100	1.00
	- 3 WAY	CCLA4K-3W	100	0.90	CCLA6K-3W	100	0.90	CCLA1LK-3W	100	1.50
	- 4 WAY	CCLA4K-4W	100	1.20	CCLA6K-4W	100	1.20	CCLA1LK-4W	100	2.00
	- 5 WAY	CCLA4K-5W	100	1.50	CCLA6K-5W	100	1.50	CCLA1LK-5W	50	1.25
	- 10 WAY	CCLA4K-10W	50	1.50	CCLA6K-10W	50	1.50	CCLA1LK-10W	25	1.25
PERMANENT SHORTING LINK	- 2 WAY	--	--	--	--	--	--	--	--	
	- 3 WAY	--	--	--	--	--	--	--	--	
	- 4 WAY	--	--	--	--	--	--	--	--	
	- 5 WAY	--	--	--	--	--	--	--	--	
	- 10 WAY	--	--	--	--	--	--	--	--	
STUD FOR PERMANENT SHORTING LINK	--	--	--	--	--	--	--	--	--	
COMB LINK	- 2 WAY	SLCM2.5 - 2W	100	0.20	SLC 6 - 2W	100	0.27	--	--	
	- 3 WAY	SLCM2.5 - 3W	100	0.30	SLC 6 - 3W	100	0.43	--	--	
	- 4 WAY	SLCM2.5 - 4W	100	0.40	SLC 6 - 4W	100	0.59	--	--	
	- 5 WAY	SLCM2.5 - 5W	50	0.25	SLC 6 - 5W	50	0.36	--	--	
	- 10 WAY	SLCM2.5 - 10W	50	0.50	SLC 6 - 10W	50	0.75	--	--	
REMOVABLE SHORTING LINK	--	--	--	--	--	--	RSL1LK	100	0.24	
STUD FOR REMOVABLE SHORTING LINK	--	--	--	--	--	--	LSR1LK	100	0.78	
MARKING LABEL	Label KN5.5	100 Strips	0.08	Label KN 8	100 Strips	0.12	Label KN 10	100 Strips	0.15	
WARNING LABEL	--	--	--	--	--	--	--	--	--	
GROUP MARKING CARRIER	SCKNMLH	50	0.55	SCKNMLH	50	0.55	SCKNMLH	50	0.55	
	SCUNMLH	50	0.60	SCUNMLH	50	0.60	SCUNMLH	50	0.60	
COLOUR:	● GREY, KHAKHI ● RED, YELLOW, BLUE ● BLACK, GREEN	KULT4(G), KULT4(K) KULT4(R), KULT4(Y), KULT4(B) KULT4(BL), KULT4(GR)	KULT6(G), KULT6(K) KULT6(R), KULT6(Y), KULT6(B) KULT6(BL), KULT6(GR)	KULT1(G), KULT1(K) KULT1(R), KULT1(Y), KULT1(B) KULT1(BL), KULT1(GR)						
MOUNTING CHANNEL	CHS 3/5/10	100/100/50	22/37/36	CHS 3/5/10	100/100/50	22/37/36	CHS 3/5/10	100/100/50	22/37/36	
STANDARD LENGTHS 300MM, 500MM, 1000MM	CHK 3/5/10	100/100/100	11/19/36	CHK 3/5/10	100/100/100	11/19/36	CHK 3/5/10	100/100/100	11/19/36	
	CHKS 3/5/10	100/100/100	11/17/34	CHKS 3/5/10	100/100/100	11/17/34	CHKS 3/5/10	100/100/100	11/17/34	
	CHKDS 10	50	34.50	CHKDS 10	50	34.50	CHKDS 10	50	34.50	


DISCONNECTING



SPRING LOADED

IEC 60947-7-1 : 800 V/20 A/4 sq mm/0.6 Nm
 : 600 V/15 A/10-24 AWG/5 Lbln
 H51(2.00"), W52(2.05"), T6(0.24")
 End Plate : KPSP4; Marking Label : KN 5.5


KSTD 6WS



SPRING LOADED

IEC 60947-7-1 : 800 V/41 A/6 sq mm/0.8 Nm
 : 600 V/35 A/8-20 AWG/12 Lbln
 H67(2.64"), W65(2.56"), T8(0.31")
 End Plate : KPSPWS; Marking Label : KN 8

KULTD 6



SPRING LOADED

IEC 60947-7-1 : 800 V/32 A/6 sq mm/1.0 Nm
 : 600 V/35 A/8-24 AWG/10 Lbln
 H55.85(2.20"), W85.4(3.36"), T8(0.31")
 End Plate : KPPLD; Marking Label : KN 8

**FOR FURTHER DETAILS
PLEASE REFER PAGE # 30 & 31**